

LOOSE COARSE THREAD SCREWS

ALPHA
DRYWALL SYSTEMS

www.alphabuildingsystems.co.uk
sales@alphabuildingsystems.co.uk
01733 309 000



Alpha Drywall System Loose Coarse Thread Screws

Alpha Coarse Screws are manufactured for use in fixing plasterboard for timber applications.

Product Information

Quantity: **1000 screws in a box**
Material: **Carbon Steel Shank with Black Phosphate coating**
Grade: **SAE C1022**
Recess Type: **Phillips 2**
Drill Point: **Sharp point**
Thread Form: **Coarse thread**
Colour: **Black**

TECHNICAL DATA

Diameter (mm)	Timber Embedment Depth		
	25mm	30mm	40mm
3.5	2,000N	N/A	N/A
4.2	3,100N	4,100N	4,900N

Ultimate Withdrawal Resistance, N_{RK} , from timber

Property	Magnitude (N)	
	3.5mm	4.2mm
Tensile Capacity, F_{ult} , R_k	6,200N	8,200N
Shear Capacity, V_{ult} , R_k	4,500N	5,300N



Product code, description and dimensions

Product Image	Product Code	Product Description	Nominal Dimensions, Dnom x Lnom (mm)	Effective Thread Length, Lthread (mm)
	STO6343	Alpha Drywall Coarse Thread 35mm	3.5mm x 35mm needle	Full
	STO6344	Alpha Drywall Coarse Thread 42mm	3.5mm x 42mm needle	Full
	STO6345	Alpha Drywall Coarse Thread 50mm	3.5mm x 50mm needle	Full
	STO6347	Alpha Drywall Coarse Thread 75mm	4.2mm x 75mm needle	50
	STO6348	Alpha Drywall Coarse Thread 100mm	4.2mm x 100mm needle	60